



**PRODUCT SPECIFICATION BULLETIN**

**SM.1000W.BU37.WDX**

**SUNMASTER®  
Warm Deluxe  
Metal Halide Grow Lamp**

---

<b>Lamp Type</b>	SINGLE ENDED METAL HALIDE
<b>Product Number</b>	80224
<b>ANSI Designation</b>	M47/E (CWA) OR REACTOR/IGNITO

---

**Performance Data**

Initial Lumens	115000
PAR Watts	345
Rated Life (Hrs. @10 Hr. / Start)	12000
Correlated Color Temperature K	3200
Chromaticity (CIE -X,Y)	.420 .395
Color Rendering Index (CRI)	65
Typical Warm Up Time (Minutes)	3-5
Typical Hot Restart Time (Minutes)	10-15
Burning Position	BASE UP ± 15°

---

**Physical Data / Requirements**

Base Designation	MOGUL (E39)
Bulb Designation	BT37
Bulb Diameter	4 5/8"
Max. Overall Length (MOL)	11 1/2"
Light Center Length (LCL)	7"
Effective Arc Length	81.5 mm
Max. Base Temperature (°C)	250
Max. Bulb Temperature (°C)	450
Luminaire Type	ENCLOSED
Socket Pulse Rating (KV)	4
Socket Style	MOGUL

---

**Electrical Data / Requirements**

Lamp Wattage	1000
Operating Voltage (Nominal)	263
Operating Current (Amps)	4.1
Min. Open Circuit Voltage (RMS)	342
Min. -Max. Starting Pulse (Peak V)	-
Min. Pulse Width At 2700 Volts (u sec)	-
Min. Pulse Rate Per 1/2 Cycle	-
Pulse Position (Min. % OCV Peak)	-

---

Revision: 10/14/2003 1940 - 1

---

**Notes**

- ▶ All electrical requirements apply when a 50 hz. reactor/ignitor system is used.

**THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30**

**Warning: This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.**